

# delta Topcoat

Recycled water based exterior paint

delta ag Ltd.

Specialist chemical products  
& anti-graffiti solutions



## Benefits

- Topcoat quickly dries to a tough, smooth, hard wearing, long lasting breathable finish
- Topcoat is ideal for economically obliterating large areas of graffiti or as a decorative finish
- Topcoat can be applied to new or aged masonry surfaces and existing paintwork
- Topcoat is available in a range of exterior colours and can be colour matched
- Topcoat is an environmentally friendly solution to the problem of waste paint disposal

## Cleaning

Clean spillages and equipment with warm soapy water followed by a clean water rinse before the product dries out. If Topcoat has been allowed to cure onto equipment then soak in Delta Activator or Graffi-sol overnight, wash in soapy water and rinse with clean water.

## Product Data

<b>Storage:</b>	Frost free
<b>Shelf Life:</b>	Minimum 6-12 Months unopened
<b>Cure Time:</b>	Touch dry 15min. Hard 60 min. @ 20oC.
<b>Recoat Interval:</b>	Allow 2-3 hours between coats
<b>Coverage:</b>	Approx 8-12 m2 per litre per coat depending upon surface porosity and profile

## An exciting new development in exterior paint finishes

Approximately 50 million litres of paint sold each year in the UK ends up unused or part used stored in sheds and garages. A large proportion of this is disposed of via landfill, an expensive and environmentally unfriendly solution to the problem.

However, Newlife Paints, the innovative new British manufacturer that pioneered emulsion paint recycling in the UK, has developed a unique process that takes waste emulsion paint and converts it instead into premium quality ecologically sound paint.

Delta in association with Newlife Paints is delighted to be able to offer Topcoat, a premium quality water based exterior paint manufactured from recycled UK sourced waste emulsion paint.

Topcoat is designed for internal or external application to new or aged masonry and existing paintwork. Topcoat exhibits excellent adhesion, opacity and covering properties making it an ideal and cost effective solution for decorative finishes or for obliterating graffiti.

## Application

- Apply to clean, dry sound surfaces.
- Apply a masonry stabiliser to dry, friable masonry surfaces.
- Remove any loose or flaking paintwork.
- Wash off any dirt and algae deposits using suitable products.
- Apply 1 – 2 coats depending on surface profile and porosity and/or intensity of underlying finish or graffiti.
- Apply Topcoat by brush, roller or spray.

Do not apply during rain or if rain is imminent.  
Do not apply if the air temperature is below 5°C.